# SCANDIC HOTELS ACCESSIBILITY STANDARDS

Here you can read our 159 point accessibility standard. It has been drawn up by carefully following the route taken by guests from the car park on through the whole hotel. We have also talked to disability organisations and guests with physical disabilities and received lots of ideas from our own keen staff. Although we rent our hotels rather than owning them, there is a lot that we can do. 105 of the 159 points are compulsory for all hotels. All 159 of the points need to be applied as we renovate or build new hotels. The standard applies in all countries in which Scandic is represented. Of course we also have to comply with the legislation in the country concerned. This means that if the legislation in the country in question is stricter on any particular point, that takes precedence.

In the cases where our standard is higher than the legislation, of course our standard applies. Our accessibility standard doesn't include everything that we actually do on the ground. Accessibility issues are incorporated as part of our day to day work, whatever the area. This means that for example, safety issues involving accessibility are in our safety standard, signs in our signage standard, and so on. In other words accessibility issues are an important part of the whole of Scandic and everyone in our team undergoes training in them.

We describe the accessibility for each individual hotel on their respective websites. We are the only hotel chain in the world to do this.

Magnus Berglund, Director of Accessibility Scandic Hotels



# PARKING AND ENTRANCE

When reconstructing
New Builidng **BEWARKS** 

1.	Disabled parking, at least 2 spaces with a minimum width of 3.6 meters each.	X		Applies only to our own car parks
2.	Accessible parking must be clearly marked with the wheelchair symbol.	X		Applies only to our own car parks
3.	Additional signage at parking bays "For assistance, please call reception on XXXX".	X		
4.	Clearly signposted and illuminated wheelchair-accessible route between parking and entrance.	X		
5.	The recommended distance to the accessible entrance is a maximum of 25 meters from		X	Applies only to our own car parks
	the car park. $\square$			
6.	Access ramps at changes of level with a maximum gradient of 1:12 at the main entrance to the	X		
	hotel and to/from the parking area. $\Box$			
7.	Contrast markings at start and end of ramps.	X		
8.	Main entrance door has a minimum width of 800 mm free clearance.	X		
9.	Main entrance door shall have a minimum width of 840 mm free clearance.		X	
10.	Low or no threshold at the entrance door for easy wheelchair access.	X		
11.	Night time doorbell accessible from wheelchair, with a sign and illuminated.	X		Height 1200 mm. Central measurement.
12.	Entrance door provided with automatic push plate, maximum height 1200 mm.		X	If door is not fully automatic.
13.	Contrast marking on electric push plate.	X		
14.	Clearly signed directions if the accessible entrance is not next to the hotel's main	X		
	entrance/building.			
15.	Contrast markings on the ground/floor (the area of the door's opening arc) are required	X		
	if there is an electric door opening system. $\square$			
16.	Contrast markings for the door.	X		
17.	Contrast markings for other glass surfaces.	X		
18.	Electronic door opener from the garage to the elevator.		X	
RI	ECEPTION			
19.	At least 2 cane holders attached to reception desk. $\square$	X		
20.	Seating and tables close to reception desk.	X		
21.	Hearing loop at reception marked with the correct sign. $\square$	X		
22.	Safety information shall be available at reception in braille or tactile. $\Box$	X		
23.	Vibrating wake up/fire alarm available to borrow, sign at reception.	X		Clear sign on reception disk
24.	Entrance carpet from entrance to reception in a different colour from flooring, or a guide line.	X		
25.	A guide line shall be provided if the reception is not immediately in front of the entrance.		X	
26.	Part of reception at a height adapted for guests in wheelchairs.		X	

LOBBY

REMARKS

	· <del></del>	_		
27.	Reachable electric socket for charging electric wheelchairs marked with a sign.		Х	Central measurement 1200 mm.
28.	Shop – clear aisles at least 800 mm wide. Products can be reached from a wheelchair. □	X		
29.	Clear walkway between reception and lift (for wheelchairs).	X		
30.	Wheelchair available to borrow.	X		The wheelchair shall be placed visible to the guests.
31.	Handheld fire extinguisher and fire extinguisher trolley in public areas. (Lobby, meeting, restaurant)		Х	
LI	FTS			
32.	Clear directions to the wheelchair accessible lift.	Х		If no all lifts are accessible.
33.	Push plate to open doors (if doors are not automatic).		X	
	Lift button and button panel inside the lift must be able to be reached from a wheelchair.	X		
	Lift buttons and button panels. Tactile buttons in each lift and on each floor.		X	
	Voice announcements for each floor and whether the lift is going up or down.		X	
	Mirror inside the lift opposite lift doors so that it is possible to see when the doors		Х	
	open/close from a wheelchair.			
M	AIN STAIRS AND STAIRS BETWEEN FLOORS			
38.	First and last steps clearly marked with a different color (contrast marking).	X		Floors + landings.
39.	Hand rails on both sides of the staircase (if staircase is wider than 105 cm). $\square$		X	
40.	Hand rails at the top and bottom of the stairs must extend 300 mm on each side		X	
	before the stairs start and end. $\square$			
41.	The hand rails must be in a contrasting colour to the background. $\Box$		X	
42.	Stone or concrete stairs must be provided with a non-slip surface on the edges of the steps. $\Box$		X	
CI	.OAKROOM			
	Some hangers/hooks must be able to be reached from a wheelchair, height 1200 mm.	Х		
M	EETING ROOMS			
44.	Door openings must be at least 800 mm.		X	
45.	There must be at least one meeting room without soft flooring (textile).		X	
46.	If the room has a telephone, it must be possible to reach this from a wheelchair.	X		
47.	Coat hangers or hooks for outdoor clothing must be able to be reached from a wheelchair,	X		
	height 1200 mm. □			
48.	Hearing loops available to borrow for meetings.	X		
49.	Permanent hearing loop in all large meeting rooms (<50 people with theatre seating).		Х	New constructions, preferably all the premises.
50.	A hearing loop must be installed in all rooms and spaces where there is		X	Only new constructions.
	microphone equipments. $\square$			
51.	A sign stating that there is a hearing loop for meetings.	X		2019-01-10 Copyright by Scandic

GUEST NEEDS / EXPECTATIONS  MEETING ROOMS		When recons New Builidng	REMARKS
52. Whiteboard fitted at maximum lowest height of 1200 mm at the bottom edge. $\Box$	X		
53. Stage – wheelchair accessible.	Х		The ramp's maximum slope < 1:12
54. Podium – alternative with wheelchair accessibility must be available.		Х	
55. Space for wheelchairs in the room, easily accessible.	Х		
56. No threshold or low threshold adapted for easy wheelchair access.	х		
BREAKOUT AREAS			
57. Seating must be available outside meeting rooms.	X		
F&B RESTAURANT AREAS			
58. Height of buffets must be 850 – 900 mm, must be able to be reached from a wheelchair.		Х	
59. Glass, china and cutlery must be able to be reached from a wheelchair.	Х		
60. There must be a separate allergy station. $\square$	X		
GUEST TOILETS (DISABLED TOILETS)			
61. Signs showing where accessible toilets are located.	X		
62. Door width at least 800 mm free clearance.	X		900 mm recommended.
63. Door width at least 840 mm free clearance.		X	900 mm recommended.
64. Rail on the inside of the door, under the handle. $\square$	X		
65. Lock with handle, see list of explanations.		X	
66. No threshold or low threshold adapted for easy wheelchair access.	X		
67. Alarm. $\square$	Х		In line with Scandic Safety & Security Manual.
68. Mirror above washbasin must be able to be used from a wheelchair.	Х		
69. Full-length mirror on the wall.		Х	
70. Contrast marking behind WC chair.		X	
71. Waste paper bin hung on the wall, can be opened from a wheelchair.	X		
72. Coat hangers/hooks can be reached from a wheelchair, height 1200 mm, and 1600 mm.	X		
WASHBASINS			
73. Washbasin's maximum height 780 mm. Top edge.	Х		
74. Empty surface immediately adjoining washbasin/WC.		х	
75. Wheelchairs must be able to fit under the washbasin.	Х		
76. Single-lever mix taps, alt. touch-free.	Х		
77. Soap dispenser, can be reached from a wheelchair.	Х		
78. Hand towels alt. electric dryers accessible from wheelchair.	Х		
79. Cane holder, x 1, height 1200 mm.		X	

When reconstructing
New Builidng
SABARKS Mandatory

Х		
Х		
	X	Only new constructions.
	X	Only new constructions.
X		
	X	
Х		
	X	In line with Scandic Safety & Security Manual.
Х		
	X	Applies to both beds.
	X	
Х		
Х		
	X	Divided 50/50 right/left.
X		
	X	Numbers to be discussed for each project.
	X	. ,
Х		
	X	
Х		
	X	
X		
Х		
X		
X		
X		
	X	
X		
	x x x x x x x x x x x x x x x x x x x	X

# MISCELLANEOUS ACCESSIBLE ROOMS

When reconstructing
New Builidng **BEWARKS** 

108.	Desk – accessible in a wheelchair. □	X		
109.	Electric socket by desk can be reached from a wheelchair.		Х	
110.	Visual fire alarm. □		X	
111.	Room thermostat placed so it can be reached from a wheelchair, central measurement 1200 mm. $\Box$		X	
112.	Mobile person hoist shall be accessible at the hotel (one per hotel).		Х	Only new constructions.
113.	If there is a safe in the room, it must be able to be reached from a wheelchair.		X	
114.	If there is a fridge/minibar in the room, it must be able to be reached from a wheelchair.		X	
115.	The keycard switch must be able to be reached from a wheelchair.		X	
ВА	THROOM ACCESSIBLE ROOMS			
116.	Free clearance at doorway into room of at least 800 mm.	X		
117.	Rail on the inside of the door, under the handle or sliding door.	X		
118.	No threshold or low threshold adapted for easy wheelchair access.	X		
119.	Alarm.	X		In line with Scandic Safety & Security Manual.
120.	Maximum height of washbasin 780 mm top edge.	X		
121.	Wheelchairs must be able to fit under the washbasin.	X		
122.	Single lever mixer tap reachable from a wheelchair.	X		
123.	Soap dispenser, can be reached from a wheelchair.	X		
124.	Towels can be reached from a wheelchair.	X		
125.	Coat hangers/hooks can be reached from a wheelchair, height 1200 mm, and 1600 mm.	X		
126.	Mirror above washbasin must be able to be seen from a wheelchair. $\Box$	X		
127.	If there is a make-up mirror, it must be able to be reached from a wheelchair. $\Box$	X		
128.	Hair dryer reachable from a wheelchair.	X		
SH	OWER			
129.	Accessible with a wheelchair.	X		
130.	Thermostat tap.	X		
131.	One shower gel/shampoo holder, can be reached from a wheelchair. $\square$	X		
132.	Empty space (maximum height 1200 mm).	X		
133.	Shower stool available.	X		
134.	Shower stool with back and arm rests compulsory with new purchasing.		X	
135.	Towels can be reached from a wheelchair.	X		
136.	Hooks must be provided at two heights. $\square$	X		
137.	Shower head must be at its lowest level when guests arrive. $\Box$	X		
138.	Shower head must be fitted at a maximum lowest height of 1200 mm. $\Box$		X	

**SHOWER** 

When reconstructing
New Builidng

BEWARKS

139. Shower curtain or glass show	er wall. 🗌	X		Depending on measurements.
140. Glass shower wall.			X	In newly built hotels, renovations or replaced where
				measurements allow.
141. Railings/handles must be prov	vided in the shower. $\square$		Х	
TOILET AREA				
142. Foldable arm rests.		X		
143. Foldable and height adjustable	e and removable armrests on both sides, see list of explanations.		X	
144. Toilet paper holder on arm res	st and on the wall. $\square$	X		
145. Contrast marking behind WC.			X	
146. Waste paper bin hung on the	wall, can be opened from a wheelchair.		X	
ALLERGY ROOMS				
147. The room must be a room wh	ere nobody has ever smoked or that has not been previously	X		
used by smokers. It must be p	possible to open a window in the room			
(a ventilation window is suffici	ent). $\square$			
148. Allergy rooms must be placed	on their own floor or corridor where we do not otherwise	X		
place guests with fur-bearing	animals. $\square$			
149. Guests with allergies must ne	ver have to encounter a dog or other fur-bearing animal outside	X		
the door or in the corridor by	the allergy room. $\square$			
150. A newly painted room cannot	be sold as an allergy room until after three months have passed,	X		
as the paint must harden first	. 🗆			
151. Allergy rooms must always ha	ve wooden floors. $\square$	X		
152. If there are loose rugs, these r	nust be taken away when the room is booked as an allergy room. $\Box$	X		
153. Pillows/quilts must be of synth	netic materials.	X		
154. The mattress must be of synth	netic materials.	X		
155. The rooms and beds must not	t have bedspreads/bed blankets or decorative cushions.	X		
156. Bedclothes and bathroom tow	rels must be washed with an eco-labeled detergent.	X		
157. Cleaning.		X		See Scandic's cleaning concept/manual.
158. Only fragrance free bathroom	products must be provided.	X		
159. Avoid fragrant flowers and pla	nts near the rooms.	Х		
			-	ı